

BRP² Doors and Frames

FEMA 361

Community Shelter Door / ICC 500

SPECIFICATIONS

Door Maximum Size 3'6" X 7'4" (single); 7' X 7'4" (pair) Frame 14 GA. Cold-rolled steel; Welded 5 ¾ Jamb Depth (Std)

Paint Prime Painted

Hinges (4) 4 1/2" Heavy Weight Butt Hinges (ANSI A156.1) **Exit Device** Surface Mounted Vertical Rod (2 point latch)

Anchors Welded Masonry Anchor Mullion Not Required for Pair

OPTIONS*

Door Types F and N

Type 316L or Type 304 Stainless Steel

ASTM A240 / A240M

Galvanized Steel ASTM A653 / A653 M - A60

Vision Panel 5" x 20" DSM Proprietary (not fire rated) Punch and Dimple (existing wall anchors) or **Anchors**

Weld-in Frame

Mortise Lock w/Deadbolt Function (ANSI A156.13) Locks

(2) Deadbolts (ANSI A156.5)

Exit Devices Surface Mounted Vertical Rod (2 point latch) or

Concealed Vertical Rod (2 point latch)

Mullion Fixed or Removable

Customizations Size, Jamb Depth, Hardware, and Other Features

8'0" Height available as single opening only with mortise lock and deadbolts. Consult factory for details.

INDEPENDENT VERIFICATION AND QUALIFICATION TESTING

Southwest Research Institute UL 752

UL / Intertek-Warnock Hersey 3 Hour Fire Resistant

Texas Tech University Wind Science and Engineering Research Center **FEMA 361**







^{*} Some options are mutually exclusive

Door & Options


Door Types







2 ACTIVE DOORS WITH EXIT DEVICES



PAIR



OPTIONS

- 1) Concealed Vertical Rod (2 point latch)
- 2) (4) Heavy Weight Butt Hinges
- 3) 5" x 20" Vision
- 4) No Mullion Required

