

FEMA 320

Residential Shelter Door

SPECIFICATIONS

Door	Maximum Size 4' X 8' 14 GA. Cold-rolled steel; 1-13/16" thick 16 GA. Perimeter Channels 12 GA. Top and Bottom Flush Caps
Frame	14 GA. Cold-rolled steel; Welded 5 3/4 Jamb Depth (Std)
Paint	Prime Painted
Hinges	(3) 4 1/2" Heavy Weight Butt Hinges (ANSI A156.1)
Locks	(1) Cylindrical Lock (ANSI A156.2) (3) Deadbolts (ANSI A156.5)
Anchors	Punch and dimple (existing wall anchors)

OPTIONS*

Door Types	F and N
Galvanized Steel	ASTM A653 / A653M – A60
Vision Panel	5" x 20" DSM Proprietary (not fire rated)
Anchors	Weld-in Frame
Locks	(1) Mortise Lock w/ Deadbolt Function (ANSI A156.13) (2) Deadbolts (ANSI A156.5)
Hinges	(4) Heavy Weight Butt Hinges (dependent on the size and weight of the door)
Customizations	Size, Jamb Depth, Hardware, and Other Features

* Some options are mutually exclusive

INDEPENDENT VERIFICATION AND QUALIFICATION TESTING

Texas Tech University
Wind Science and Engineering
Research Center
FEMA 320

DeanSteel Manufacturing Company
931 S. Flores Street
San Antonio, TX 78204

P 800.825.8271
F 210.226.0913
www.DeanSteel.com



MADE IN AMERICA
AND VETERAN OWNED

Door Types



F
FLUSH



N
NARROW VISION

Door & Options



OPTIONS

- 1) Mortise lock w/Deadbolt Function and 2 Deadbolts
- 2) (4) Heavy Weight Butt Hinges
- 3) 5" x 20" Vision

DOOR HANDING CHART				NOTE : ALWAYS USE THE KEY SIDE OF THE DOOR FOR REFERENCE	
SINGLE DOORS		PAIR OF DOORS			
<p>INSIDE</p> <p>RIGHT HAND RH</p>	<p>INSIDE</p> <p>LEFT HAND LH</p>	<p>INSIDE</p> <p>RIGHT HAND ACTIVE RH ACT</p>	<p>INSIDE</p> <p>LEFT HAND ACTIVE LH ACT</p>		
<p>INSIDE</p> <p>RIGHT HAND REVERSE RHR</p>	<p>INSIDE</p> <p>LEFT HAND REVERSE LHR</p>	<p>INSIDE</p> <p>RIGHT HAND REVERSE ACTIVE RHR ACT</p>	<p>INSIDE</p> <p>LEFT HAND REVERSE ACTIVE LHR ACT</p>		